







- Clean Face Look No Louvers
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 17½" x 19¾", 345½ in²
- High Definition Log Set
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty
- Quick Access Valve Controls

Available Options

- Remote or Thermostat Control
- Glass, Coal, or Log Set
- Liners Options:
- Brick Liner with Logs
- Black Enameled Liner with Glass or Logs
- Ledgestone Liner
- Surround Options:
- Modern Surround
- Contemporary Surround. w/Trimmable Panel
- Trimmable Panel

Insert Specifications

BTU Maximum Input - NG	2	0,000 BT	U	
BTU Minimum Output*	7,900 BTU			
Heating Area	1,000 ft ²			
P4 Efficiency	74.5%			
Glass Size	345½ in²			
Minimum Install Dims.	HEIGHT 27½"	DEPTH 14¼"		

^{*} Turn down is based on a 50% valve and AFUE efficiencies output.



High Definition Log Set



Coal



Glass Burner with Crushed Glass





- Clean Face Look No Louvers
- Cast Iron Heat Exchanger
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 21¾" x 13¾", 300 in²
- High Definition Log Set
- Easy Access Burner Switch
- 110 CFM Room Fan (with variable control)
- Limited Lifetime Warranty

Available Options

E20 Fireplace Insert – Extruded Plus Surround Panel, Fluted Liner, and Log Set

- Hearth Riser
- Remote or Thermostat Control
- Glass or Log Set
- Liner Options:
- Brick or Fluted Liner with Logs
- Black Enameled Liner with Glass or Logs
- Surround Options:
- Modern Surround
- Contemporary Surround
- Slim Surround
- Extruded Surround
- 4-Sided Extruded Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

BTU Maximum Input - NG	2	3,000 BT	U
BTU Minimum Output*	3	3,000 BTU	J
Heating Area		1,200 ft ²	
P4 Efficiency		66.45%	
Glass Size		300 in ²	
Minimum Install Dims.	HEIGHT 181⁄4″	WIDTH 241/4"	DEPTH 14"

^{*} Turn down is based on a 50% valve and AFUE efficiencies output.



Fluted Liner with Log Set



Black Glass with Decorative Stones



Brick Liner with Log Set







- Clean Face Look No Louvers
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 26¼" x 16", 420 in²
- High Definition Log Set
- Easy Access Burner Switch
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty

Available Options

- Hearth Riser
- Remote or Thermostat Control
- Glass, Log Set, or Driftwood
- Liners Options:
- Brick Liner (Log Burner)
- Black Enameled Liner (Glass or Log Burner)
- Fluted Liner (Log Burner)
- Ledgestone Liner (Log Burner)
- Surround Options:
- Modern Surround - Contemporary Surround
- Slim Surround
- Extruded Surround
- 4-Sided Extruded Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

ı			
BTU Maximum Input - NG	3	3,000 BT	U
BTU Minimum Output*	1	0,000 BT	U
Heating Area		1,700 ft ²	
P4 Efficiency		71.4%	
Glass Size		420 in ²	
Minimum Install Dims.	HEIGHT 19 1/8"	WIDTH 27%"	DEPTH 16"

^{*} Turn down is based on a 50% valve and AFUE efficiencies output.



Brick Liner with Log Set



Glass Burner with Diamond Glass



Black Enameled Liner with Driftwood







- Top Firebox Lighting
- Adjustable Ember Bed Lighting
- Clean Face Look No Louvers
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 261/4" x 16", 420 in²
- Ultra High Definition Log Set
- 150 CFM Room Fan (with variable control)
- Run-Quiet Fan System
- Limited Lifetime Warranty



Available Options

- Hearth Riser
- Remote or Thermostat Control
- Ultra High Definition Log Set
- Liners Options:
 Brick | Black Enameled | Fluted | Ledgestone
- Surround Options:
- Contemporary Surround
- Slim Surround
- Extruded Surround
- 4-Sided Extruded Surround
- Designer Series Surround
- Cast Plus Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

BTU Maximum Input - NG	3	2,500 BT	U	
BTU Minimum Output*	16,000 BTU			
Heating Area		1,700 ft ²		
P4 Efficiency	75.4%			
Glass Size		420 in ²		
Minimum Install Dims.	HEIGHT 19 1/8"	DEPTH 16"		

^{*} Turn down is based on a 33% valve and P4 efficiencies output.



Ultra HD Log Set with Brick Liner



Designer Series Surround



Adjustable Ember Bed Lighting







- Clean Face Look No Louvers
- SIT Valve 820 (Standing Pilot)
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 28½" x 18", 513 in²
- High Definition Log Set
- Easy Access Burner Switch
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty
- Quick Access Valve Controls Contemporary and Extruded Panels Only

Available Options

- Hearth Riser
- Remote or Thermostat Control
- Glass, Log Set, Driftwood, or Ceramic Rock Set
- Liners Options:
- Brick Liner (Log Burner)
- Black Enameled Liner (Glass or Log Burner)
- Fluted Liner (Log Burner)
- Ledgestone Liner (Log Burner)
- Surround Options:
- Modern Surround
- Contemporary Surround
- Slim Surround
- Extruded Surround
- Trimmable Panel
- ELITE EDITION SURROUND PANELS

Insert Specifications

BTU Maximum Input - NG	3	4,000 BT	U	
BTU Minimum Output*	11,000 BTU			
Heating Area		1,800 ft ²		
P4 Efficiency	71.1%			
Glass Size		513 in ²		
Minimum Install Dims.	HEIGHT 20"	WIDTH 32"	DEPTH 17½"	

^{*} Turn down is based on a 50% valve and AFUE efficiencies output.



Midnight Bronze Forgeworks Surround



Ceramic Rock Set



Log Set with Ledgestone Liner







- Firebox Top Lighting
- Adjustable Ember Bed Lighting
- Clean Face Look No Louvers
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 28½" x 18", 513 in²
- Ultra High Definition Log Set
- 150 CFM Room Fan (with variable control)
- Run-Quiet Fan System
- Limited Lifetime Warranty



Available Options

- Hearth Riser
- Remote or Thermostat Control
- Ultra High Definition Log Set
- Liners Options:
 Brick | Black Enameled | Fluted | Ledgestone
- Surround Options:
- Contemporary Surround
- Slim Surround
- Extruded Surround
- Designer Series Surround
- Cast Plus Surround
- Trimmable Panel
 ELITE EDITION SURROUND PANELS

Insert Specifications

BTU Maximum Input - NG	3	5,000 BT	U	
BTU Minimum Output*	17,000 BTU			
Heating Area	1,800 ft ²			
P4 Efficiency	74.5%			
Glass Size	513 in ²			
Minimum Install Dims.	HEIGHT 20"	WIDTH 32"	DEPTH 17½"	

^{*} Turn down is based on a 33% valve and P4 efficiencies output.



Firebox Top Lighting (Left=On, Right=Off)



Ultra HD Log Set with Fluted Liner



Cast Plus Surround







- Clean Face Look No Louvers
- SIT Valve 885 (IPI System with Remote)
- Glass Size: 30 5/8" x 22 1/4", 681 in2
- High Definition Log Set
- Remote Control Included
- 150 CFM Room Fan (with variable control)
- Limited Lifetime Warranty

Available Options

- Hearth Riser
- Thermostat Control
- Liners Options:Brick | Black Enameled | Fluted | Ledgestone
- Surround Options:
- Modern Surround
- Cape Cod Doors
- Contemporary Surround
- Extruded Surround
- Borderview Surround | ELITE EDITION
- 4-Sided Extruded Surround
- Trimmable Panel

Insert Specifications

BTU Maximum Input - NG	4	2,000 BT	U	
BTU Minimum Output*	13,000 BTU			
Heating Area		2,300 ft ²		
P4 Efficiency	63%			
Glass Size	681 in ²			
Minimum Install Dims.	HEIGHT 24"	DEPTH 203/8"		



Cape Cod Doors







Log Set with Ledgestone Liner

* Turn down is based on a 33% valve and AFUE efficiencies output.

Surround Panels

ELITE EDITION | SURROUND PANELS



CONTEMPORARYAvailable for the E20, E30, E33, EX32, EX35, & E44



Available for the E20, E30, E33, & E44



BORDERVIEWAvailable for the E20, E30, E33, EX32, EX35 & E44 (E44 only in Brushed Nickel)
Brushed Nickel • Brushed Antique Copper • Powder Coated Grey



BORDERVIEW PLUS

Available for the E20, E30, E33, EX32 & EX35

Brushed Nickel • Brushed Antique Copper • Powder Coated Grey



SLIMAvailable for the E20, E30, E33, EX32 & EX35



EXTRUDEDAvailable for the E20, E30, E33, EX32, EX35, & E44



DESIGNER SERIES SURROUND

Available for the EX32 & EX35

Brushed Nickel • Brushed Antique Copper • Powder Coated Grey

Powder Coated Silver • Powder Coated Bronze



MODERN PLUS

Available for the E20, E30, E33, EX32 & EX35

Powder Coated Grey



CAPE COD DOORSAvailable for the E44



4 - SIDED EXTRUDEDAvailable for the E20, E30, & E44



EXTRUDED PLUSAvailable for the E20, E30, E33, EX32 & EX35
Powder Coated Grey



Available for the E30, E33, EX32 & EX35 Midnight Bronze



Q1 MODERNAvailable for the Q1



CONTEMPORARY W/TRIMMABLE PANEL
Available for the Q1



Available for the E20 & E30
Powder Coated Grey




CAST PLUS SURROUNDAvailable for the EX32 & EX35

Unit Specifications

Performance	Q1 PORTRAIT GAS INSERT	E20 SMALL GAS INSERT	E30 / EX32 MEDIUM GAS INSERTS	E33 / EX35 LARGE GAS INSERTS	E44 EXTRA LARGE GAS INSERT
BTU Maximum input - NG / LP	20,000 / 18,500	23,000 / 21,300	E30 - 33,000 / 28,000 EX32 - 32,500 / 31,000	E33 - 34,000 / 31,000 EX35 - 35,000 / 35,000	42,000 / 36,000
Turn Down - Valve 820 / Valve 885	50% / 33%	50% / 33%	50% / 33%	50% / 33%	N/A / 33%
Heat Exchanger	Steel	Cast Iron	Steel	Steel	Steel
SIT Valve 820 (Standing Pilot)	Available	Available	E30: Available / EX32: N/A	E33: Available / EX35: N/A	N/A
SIT Valve 885 (IPI)	Available	Available	E30: Available / EX32: Standard	E33: Available / EX35: Standard	Available
Efficiency - Steady State*	76.19%	72.39%	E30: 78.72% / EX32: 73.48%	E33: 77.64% / EX35: 76.1%	82%
Efficiency - FE rating [†]	74.45%	66.45%	E30: 71.4% / EX32: 75.47%	E33: 71.13% / EX35: 74.54%	63%
Glass Size	17½" x 19¾", 345½ in²	21¾" x 13¾", 300 in²	261/4" x 16", 420 in ²	28½" x 18", 513 in²	30 ³ / ₄ " x 22 ¹ / ₄ ", 681 in ²
Convection Fan	150 CFM	110 CFM	150 CFM	150 CFM	150 CFM

Installation	Q1 PORTRAIT GAS INSERT	E20 SMALL GAS INSERT	E30 / EX32 MEDIUM GAS INSERTS	E33 / EX35 LARGE GAS INSERTS	E44 EXTRA LARGE GAS INSERT	
Min. Install Dims.	HEIGHT WIDTH DEPTH 27 1/2" 20 1/4" 14 1/4"	HEIGHT WIDTH DEPTH 181/4" 241/4" 14"	HEIGHT WIDTH DEPTH 19 1/8" 27 1/8" 16"	HEIGHT WIDTH DEPTH 20" 32" 171/2"	HEIGHT WIDTH DEPTH 24" 34 ½" 20 3/8"	
LP Conversion Kit (SP)	Standard	Standard	E30: Standard / EX32: N/A	E33: Standard / EX35: N/A		
LP Conversion Kit (IPI)	Optional	Optional	Optional	Optional	Optional	
Venting (Direct Vent)	3" x 3"	3" x 2"	3" x 3"	3" x 3"	3" x 3"	
Weight	170 lbs	90 lbs	116 lbs	135 lbs	210 lbs	
Wood ZC Fireplace Approved	Standard	Standard	Standard	Standard	Standard	
ZC Floor Removal Approved	Standard		E30: 2¼" Raise / EX32: ½" Raise	E33: 4" Raise / EX35: 3½" Raise		

Clearance to Combustibles	Q1	E20	E30 / EX32	E33 / EX35	E44
A - center of unit to side wall	16½"	19½"	21″	24"	23½"
B - bottom of unit to bottom of 12" mantle	41"	39¾"	36" (EX32 42")	36"	40"
C - unit bottom to max. 3/4" combustible facing	351/4"	37½"	30" (EX32 33")	30"	40"
D - center of unit to side facing	10"	16½"	21″	23"	23"
E - front of door to edge of floor protection	12"	13"	16" (EX32 9")	16" (EX35 9")	16"‡



Available Options

Surround Panels		1 GAS INSERT		20 AS INSERT		EX32 AS INSERTS		EX35	E4 EXTRA LARG	14 E GAS INSERT
Contemporary Surround	HEIGHT	WIDTH	HEIGHT 23 7/8"	WIDTH 35 3/8"	HEIGHT 25"	WIDTH 39 3/4"	HEIGHT 261/2"	WIDTH 44 ½"	HEIGHT 30 ½"	WIDTH 45"
Oversize Contemporary Surround			26 7/8"	37 3/8"	29"	397/8"	29"	441/8"		
Extruded Surround			23 7/8"	35 3/8"	25 1/8"	39¾"	261/2"	441/8"	30 1/8"	45"
Oversize Extruded Surround					29"	39¾"	29"	441/8"		
Modern Surround	30"	30"	23 7/8"	35 3/8"					30 1/8"	45"
Slim Surround			21"	29¾"	22"	33 1/4"	22 1/4"	36"		
Cape Cod Doors									30"	42"
4-Sided Extruded Surround			29 5/8"	35 3/8"	31½"	39¾"			37"	45"
Contemporary Sur. w/Trimmable Panel	32"	36"								
Borderview Surround – EE			24"	37 1/4"	26 1/8"	40"	25 1/8"	42"	283/4"	45"
Borderview Plus Surround - EE			24"	37 1/4"	26 1/8"	40"	25 1/8"	42"		
Extruded Plus Surround - EE			24 1/8"	367/8"	26"	40"	25 1/8"	42"		
Modern Plus Surround – EE			225/8"	341/4"	25 3/8"	381/2"	245/8"	39"		
Borderview Plus 4S Surround - EE			26 7/8"	35¾"	31"	40"				
Forgeworks Surround – EE					26 1/8"	40"	25 1/8"	42"		
Designer Series Surround – EE EX32/EX35 Only					241/2"	385/8"	25"	41 ¾"		
Oversize Designer Series Surround – EE EX32/EX35 Only					30	43 ¾"	30"	45 3/4"		
Cast Plus Surround – EE EX32/EX35 Only					243/4"	393/8"	25 1/4"	42 1/4"		
Oversize Cast Plus Surround - EE EX32/EX35 Only					30	393/8"	32"	43 3/4"		
Trimmable Panel	32"	36"	28¾"	41 ¾"	38"	46"	38"	46"	36"	55"
4-Sided Trimmable Panel			393/8"	41 3/4"	41 1/8"	46"			47"	55"
Firebox Liners		21 GAS INSERT		20 AS INSERT	,	EX32 AS INSERTS	•	EX35	E 4	14 E GAS INSERT
Brick Liner	•	/	•	/	•	/	•	/		/
Black Enameled Steel Liner	•	/	•	/	•	/	•	/		/
Fluted Liner				/	•	/	1	/	•	/
Ledgestone Liner	`				`		•	/		
Burner Variations		21 GAS INSERT		20 AS INSERT		EX32 AS INSERTS		EX35	E4	14 E GAS INSER
High Definition Log Set (Ultra HD for EX32/EX35)		/		,		/	1	/		,

Black Enameled Steel Liner	~	~	~	V	V
Fluted Liner		~	✓	~	✓
Ledgestone Liner	~		~	~	✓
Burner Variations	Q1 PORTRAIT GAS INSERT	E20 SMALL GAS INSERT	E30 / EX32 MEDIUM GAS INSERTS	E33 / EX35 LARGE GAS INSERTS	E44 EXTRA LARGE GAS INSERT
High Definition Log Set (Ultra HD for EX32/EX35)	✓	~	~	~	✓
Driftwood Log Set			E30 Only	E33 Only	
Glass Burner (Black Glass)	Crushed Glass	Diamond Glass	Diamond Glass	Diamond Glass	
Ceramic Rock Set				E33 Only	

Additional Options	Q1 PORTRAIT GAS INSERT	E20 SMALL GAS INSERT	E30 / EX32 MEDIUM GAS INSERTS	E33 / EX35 LARGE GAS INSERTS	E44 EXTRA LARGE GAS INSERT
Decorative Stones (Glass Tray Burners Only)		~	~		
Firebox Lights (Top & Bottom)			EX32 Standard	EX35 Standard	
Hearth Riser (N/A with 4-Sided Surround Panels)		2"H 403/4"W	2"H 43½"W	2"H 45½"W	1½"H 46¾"W
Programmable Thermostat	✓	~	✓	✓	✓
Proflame Remote Control	Standard with IPI Optional with 820 Nova	Optional	Standard with IPI Optional with 820 Nova	Standard with IPI Optional with 820 Nova	Standard

^{*} Steady State based on measured rating of IPI model.

[†] FE Rating based on measured P.4 rating of IPI model.

[‡] Based on a minimum ½" raised hearth (18" flush).

EE Elite Edition Surround Panel

The best way to visualize your dream fireplace at home is with the Enviro App!

















